



## Indoor Coverage for 800 MHz LTE Applications

### Product Classification

**Product Type** RF repeater unit

### General Specifications

**Antenna Interface at Repeater** SMA Female

**Indoor Antenna** Optional, not included

**Optional Antenna Gain** 2 dBi

**Optional Antenna Type** Omni

**Performance Note** Values typical, unless otherwise stated

**Supervision/Control Option** Heartbeat via SMS | Remote control

### Dimensions

**Height** 240 mm | 9.449 in

**Width** 240 mm | 9.449 in

**Depth** 35 mm | 1.378 in

**Optional Antenna Length** 80 mm | 3.15 in

### Electrical Specifications

**Gain, typical** 70 dB

**Gain Adjustment Range** 30 dB

**License Band** LTE 800

**Local Power** 6 Vdc

**Mains Power** 100–240 Vac

**Return Loss** 10 dB

**Power Consumption** 20 W

### Electrical Specifications, Rx (Uplink)

**Operating Frequency Band** 832 – 862 MHz

# 7657462 | MR818

---

**Output Power @ One Carrier** 18 dBm (3GPP)

**Output Power @ Two Carriers** 15 dBm (3GPP)

## Electrical Specifications, Tx (Downlink)

**Operating Frequency Band** 791 – 821 MHz

**Output Power @ One Carrier** 18 dBm (3GPP)

**Output Power @ Two Carriers** 15 dBm (3GPP)

## Environmental Specifications

**Operating Temperature** +5 °C to +40 °C (+41 °F to +104 °F)

**Ingress Protection Test Method** IEC 60529:2001, IP30

## Packaging and Weights

**Weight, net** 1.5 kg | 3.307 lb

## Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Above maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant/Exempted
UK-ROHS	Compliant/Exempted

