

# TEL-SPLICE II Portfolio

Tel-Splice II connectors provide an economical and reliable means of splicing telephone cable conductors. The conductors are available in several configurations for different applications like load coils, stub cables, ready access terminals and trunk and tool cables.



## Features

- **Durable** – Highly resistant to moisture and chemical attack; flame retardant models available.
- **Economical** – Lower applied cost; IDC (installation displacement connectors), gas tight connections, no prestripping required, means minimal operator preparation.
- **Versatile** – Available filled or unfilled; color coded for easy identification: 2-wire, 3-wire and tap in loose piece.
- **Gel-filled** connectors for environmentally protected connections.

## General attributes & characteristics

- Product specifications
  - RUD 5569 A -TS for Tel-splice and Amp Stack
- All variants are gel-filled
- Conductor range 0.4 – 0.9mm

## Design and configurations

| Product Description | Housing color | Application | Conductor range | Insulation |
|---------------------|---------------|-------------|-----------------|------------|
| Tel-Splice II Y2F   | Yellow        | 2-Wire      | 0.4-0.9mm       | 2.08mm     |
| Tel-Splice II RF    | Red           | 2 or 3-Wire | 0.4-0.9mm       | 2.08mm     |
| Tel-Splice II BF    | Green         | Half Tap    | 0.4-0.9mm       | 1.67mm     |

## Product offering - Tel-Splice II

| Order Number | Description       | MOQ   |
|--------------|-------------------|-------|
| CK1828-001   | Tel-Splice II Y2F | 10000 |
| CK1830-001   | Tel-Splice II RF  | 10000 |
| CS5638-001   | Tel-Splice II BF  | 10000 |

## Product offering - Tel-Splice II tooling accessories

| Order Number | Description            |
|--------------|------------------------|
| 9-790162-1   | TEL SPLICE TOOLING KIT |

